Engineering Development Model

Voltage Controlled Oscillator

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.

Please click "Back", and then click "Contact Us" for Applications support.

ROS-EDR11006



CASE STYLE: CK1113

ELECTRICAL SPECIFICATIONS 50Ω				
Parameter	Min.	Typ.	Max.	Units
Frequency	3200		3200	MHz
Tuning Voltage	0.5		5.0	V
Power Output		+6.5		dBm
Phase Noise			4	
at 1 kHz offset		-89		dBc/Hz
at 10 KHz offset		116		dBc/Hz
at 100 KHz offset	0	-135		dBc/Hz
at 1000 kHz offset	2	-155		dBc/Hz
Pulling at 12 dBr PK-PK all phases	.4	0.5		MHz
Pushing at Vcc=8V±0.4V		0.1		MHz/V
Tuning Sensitivity	10	10		MHz/V
Harmonic Suppression	4	-33	-26	dBc
3 dB Modulation Bandwidth		140000		kHz
Supply Voltage		8		V
Supply Current			32	mA

MAXIMUM RATINGS		
Operating Temperature	-55°C to 85°C	
Storage Temperature	-55°C to 100°C	
Absolute Supply Voltage (Vcc)	+10V	
Absolute Tuning Voltage (Vtune)	+7V	

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	

140630