## Engineering Development Model

## **Voltage Controlled Oscillator**

## **ROS-EDR11010MP**

## **Important Note**

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

**CASE STYLE: CK605** 

ELECTRICAL SPECIFICATIONS 50Ω				
Parameter	Min.	Тур.	Max.	Units
Frequency	2958		2982	MHz
Tuning Voltage	0.5		4.5	V
Power Output	0	+4.5		dBm
Phase Noise at 1 kHz offset		70	•	dBc/Hz
at 10 KHz offset		-96		dBc/Hz
at 100 KHz offset at 1000 kHz offset		-117 -137		dBc/Hz dBc/Hz
Pulling at 12 dBr PK-PK all phases		1.2		MHz
Pushing at Vcc=5V±0.25V		2.2	W(2)	MHz/V
Tuning Sensitivity		92		MHz/V
Harmonic Suppression		-22	-15	dBc
3 dB Modulation Bandwidth		360000		kHz
Supply Voltage	0 4	5		V
Supply Current		0	39	mA

MAXIMUM RATINGS			
Operating Temperature	-55°C to 85°C		
Storage Temperature	-55°C to 100°C		
Absolute Supply Voltage (Vcc)	+7V		
Absolute Tuning Voltage (Vtune)	+6.5V		

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	