## Engineering Development Model

## **Voltage Controlled Oscillator**

## ROS-EDR9204

## **Important Note**

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

**CASE STYLE: CK605** 

ELECTRICAL SPECIFICATIONS 50Ω					
Parameter	Min.	Тур.	Max.	Units	
Frequency	4000		4160	MHz	
Tuning Voltage	0.5		4.9	V	
Power Output		+1.5		dBm	
Phase Noise					
at 1 kHz offset		-76		dBc/Hz	
at 10 KHz offset		-105		dBc/Hz	
at 100 KHz offset		-127		dBc/Hz	
at 1000 kHz offset		-147		dBc/Hz	
Pulling at 12 dBr PK-PK all phases		1		MHz	
Pushing at Vcc=5V±0.25V		0.1		MHz/V	
Tuning Sensitivity		56 - 64		MHz/V	
Harmonic Suppression		-30	-21	dBc	
3 dB Modulation Bandwidth		80000		kHz	
Supply Voltage		5		V	
Supply Current			35	mA	

MAXIMUM RATINGS			
Operating Temperature	-55°C to 85°C		
Storage Temperature	-55°C to 100°C		
Absolute Supply Voltage (Vcc)	+7V		
Absolute Tuning Voltage (Vtune)	+6.9V		

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and means rement instructions.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"): Purchasers of this part are entitled to the legits and brieflits contained therein. For a full statement of the Standard Terms and the excluse rights and remodes thresunder, please with Mini-Circuit's website at www.minicircuits.com/MCL3/contemp.jp.