## Engineering Development Model

## **Voltage Controlled Oscillator**

## ROS-EDR9293

## **Important Note**

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

**CASE STYLE: CK605** 

ELECTRICAL SPECIFICATIONS 50Ω					
Parameter	Min.	Тур.	Max.	Units	
Frequency	4550		5150	MHz	
Tuning Voltage	0.5		15.0	V	
Power Output		0		dBm	
Phase Noise					
at 1 kHz offset		-64		dBc/Hz	
at 10 KHz offset		-90		dBc/Hz	
at 100 KHz offset		-113		dBc/Hz	
at 1000 kHz offset		-134		dBc/Hz	
Pulling at 12 dBr PK-PK all phases		0.9		MHz	
Pushing at Vcc=5V±0.25V		6.3		MHz/V	
Tuning Sensitivity		44 - 55		MHz/V	
Harmonic Suppression		-26	-11	dBc	
3 dB Modulation Bandwidth		115000		kHz	
Supply Voltage		5		V	
Supply Current			40	mA	

MAXIMUM RATINGS			
Operating Temperature	-55°C to 85°C		
Storage Temperature	-55°C to 100°C		
Absolute Supply Voltage (Vcc)	+7V		
Absolute Tuning Voltage (Vtune)	+17V		

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of the specification document. By Exercise the specification document are intended to be excluded and do not form a part of the specification document.

B. Exercise in this specification and the specification of the specification o

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. C. The parts covered by this specification document are subject to Mini-Circuit's standard firmided warranty and terms and conditions jookedwey, "Standard Terms"; Purchasers of this part are entitled to the eights and benefits critianed therms. For a full statement of the Standard Terms and encodes thereunder, please with Mini-Circuit's website at www.miniciouits.com/MC.Store-terms.jap