Engineering Development Model

Voltage Controlled Oscillator

ROS-EDR9339/2

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE: CK829

ELECTRICAL SPECIFICATIONS 50Ω					
Parameter	Min.	Тур.	Max.	Units	
Frequency	1280		1280	MHz	
Tuning Voltage	1		10.0	V	
Power Output		+7		dBm	
Phase Noise					
at 1 kHz offset		-87		dBc/Hz	
at 10 KHz offset		-115		dBc/Hz	
at 100 KHz offset		-137		dBc/Hz	
at 1000 kHz offset		-157		dBc/Hz	
Pulling at 12 dBr PK-PK all phases		1.3		MHz	
Pushing at Vcc=8V±0.4V		0.1		MHz/V	
Tuning Sensitivity		2		MHz/V	
Harmonic Suppression		-17		dBc	
3 dB Modulation Bandwidth		65000		kHz	
Supply Voltage		8		V	
Supply Current			34	mA	

MAXIMUM RATINGS			
Operating Temperature	-55°C to 85°C		
Storage Temperature	-55°C to 100°C		
Absolute Supply Voltage (Vcc)	+10V		
Absolute Tuning Voltage (Vtune)	+12V		

PIN CONNECTIONS			
RF OUT	10		
VCC	14		
V-TUNE	2		
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16		

Notes

A. Putrimines and quality attributes and conditions not exceesily stated in this specification document are intended to be excluded and do not form a part of this specification document.

A Performance and quality attributes and conditions not expressly stated in this specification abcoursert are intermibled to be excluded and do not form a part of this specification advantage of the specification and performance citizened in this specification decoursert are based on Mini-Critical is applicable established test performance citizenia and measurement instructions.

C. The parts covered by this specification document are subject to Mini-Cricuits standard limited warranty and terms and conditions [collectively, "Standard Terms"): Purchasers of this part are entitled.