Engineering Development Model

Voltage Controlled Oscillator

ROS-EDR9595

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE: CK605

ELECTRICAL SPECIFICATIONS 50Ω					
Parameter	Min.	Тур.	Max.	Units	
Frequency	2400		4000	MHz	
Tuning Voltage	0.25		18.0	V	
Power Output		+4		dBm	
Phase Noise					
at 1 kHz offset		-62		dBc/Hz	
at 10 KHz offset		-88		dBc/Hz	
at 100 KHz offset		-110		dBc/Hz	
at 1000 kHz offset		-130		dBc/Hz	
Pulling at 12 dBr PK-PK all phases		3.2		MHz	
Pushing at Vcc=12V±0.6V		1.4		MHz/V	
Tuning Sensitivity		60 - 137		MHz/V	
Harmonic Suppression		-29	-10	dBc	
3 dB Modulation Bandwidth		130000		kHz	
Supply Voltage		12		V	
Supply Current			38	mA	

MAXIMUM RATINGS			
Operating Temperature	-55°C to 85°C		
Storage Temperature	-55°C to 100°C		
Absolute Supply Voltage (Vcc)	+14V		
Absolute Tuning Voltage (Vtune)	+20V		

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	

Notes

A performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data confiamed in this specification document are based on Min-Coructs applicable established test performance criteria and measurement instructions.

C. The parts converted by this specification document are subject to Min-Coructs tamped invited invited wearantly and terms and conditions [codectively. "Standard Terms"]. Purchasers of this part are entitled.