Engineering Development Model

Voltage Controlled Oscillator

ROS-EDR9599

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE: CK605

ELECTRICAL SPECIFICATIONS 50Ω					
Parameter	Min.	Тур.	Max.	Units	
Frequency	5315		5326	MHz	
Tuning Voltage	1.5		4.0	V	
Power Output		+7		dBm	
Phase Noise					
at 1 kHz offset		-69		dBc/Hz	
at 10 KHz offset		-97		dBc/Hz	
at 100 KHz offset		-119		dBc/Hz	
at 1000 kHz offset		-138		dBc/Hz	
Pulling at 12 dBr PK-PK all phases		1.4		MHz	
Pushing at Vcc=5.5V±0.275V		0.04		MHz/V	
Tuning Sensitivity		39 - 40		MHz/V	
Harmonic Suppression		-26	-18	dBc	
3 dB Modulation Bandwidth		140000		kHz	
Supply Voltage		5.5		V	
Supply Current			55	mA	

MAXIMUM RATINGS			
Operating Temperature	-55°C to 85°C		
Storage Temperature	-55°C to 100°C		
Absolute Supply Voltage (Vcc)	+7.5V		
Absolute Tuning Voltage (Vtune)	+6V		

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical inspecifications in earl performance chair condensed in this recollication document are based on Min-Climatia and previous expression of the performance criteria and means removed in this recollection.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"): Purchasers of this part are entitled to the legits and brieflits contained therein. For a full statement of the Standard Terms and the excluse rights and remodes thresunder, please with Mini-Circuit's website at www.minicircuits.com/MCL3/contemp.jp.