
## Engineering Development Model

## **Voltage Controlled Oscillator**

## **ROS-EDR9609/2**

## **Important Note**

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

**CASE STYLE: CK605** 

| ELECTRICAL SPECIFICATIONS 50Ω      |       |              |      |           |
|------------------------------------|-------|--------------|------|-----------|
| Parameter                          | Min.  | Тур.         | Max. | Units     |
| Frequency                          | 3.18  | 6            | 3.69 | MHz       |
| Tuning Voltage                     | 1     |              | 6    | V         |
| Power Output                       |       | 0            |      | dBm       |
| Phase Noise                        |       | 000          |      | JD - // J |
| at 1 kHz offset                    |       | -90          |      | dBc/Hz    |
| at 10 KHz offset                   |       | -119         |      | dBc/Hz    |
| at 100 KHz offset                  |       | -147         |      | dBc/Hz    |
| Pulling at 12 dBr PK-PK all phases |       | 19.8         |      | kHz       |
| Pushing at Vcc≠12V±0.6V            | 07    | 39.4         |      | kHz/V     |
| Tuning Sensitivity                 |       | 197 - 213    |      | kHz/V     |
| Harmonic Suppression               |       | <b>7.</b> 57 | -41  | dBc       |
| Supply Voltage                     |       | 12           |      | V         |
| Supply Current                     | 10 60 | •            | 38   | mA        |

| MAXIMUM RATINGS                 |                |  |  |
|---------------------------------|----------------|--|--|
| Operating Temperature           | -55°C to 85°C  |  |  |
| Storage Temperature             | -55°C to 100°C |  |  |
| Absolute Supply Voltage (Vcc)   | +14V           |  |  |
| Absolute Tuning Voltage (Vtune) | +8V            |  |  |

| PIN CONNECTIONS |                                |  |
|-----------------|--------------------------------|--|
| RF OUT          | 10                             |  |
| VCC             | 14                             |  |
| V-TUNE          | 2                              |  |
| GROUND          | 1,3,4,5,6,7,8,9,11,12,13,15,16 |  |

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits applicable established test performance criteria and measurement instructions.

C. The parts covered by this specification document are subject to Mini-Circuits standard imitted warrantly and terms and conditions (collectively, "Standard Terms"); Purchasers or this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp