Engineering Development Model

Voltage Controlled Oscillator

ROS-EDR9618

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE: CK829

ELECTRICAL SPECIFICATIONS 50Ω					
Parameter	Min.	Тур.	Max.	Units	
Frequency	2400		4500	MHz	
Tuning Voltage	0.25		18.0	V	
Power Output		+6		dBm	
Phase Noise					
at 1 kHz offset		-56		dBc/Hz	
at 10 KHz offset		-82		dBc/Hz	
at 100 KHz offset		-106		dBc/Hz	
at 1000 kHz offset		-128		dBc/Hz	
Pulling at 12 dBr PK-PK all phases		10.4		MHz	
Pushing at Vcc=10V±0.5V		1.9		MHz/V	
Tuning Sensitivity		50 - 257		MHz/V	
Harmonic Suppression		-17		dBc	
Supply Voltage		10		V	
Supply Current			60	mA	

MAXIMUM RATINGS		
Operating Temperature	-55°C to 85°C	
Storage Temperature	-55°C to 100°C	
Absolute Supply Voltage (Vcc)	+12V	
Absolute Tuning Voltage (Vtune)	+20V	

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	

Notes.

Electrical specificacion of quality attractes and conditions not expressly stated in this specification obcurrent, as electrical periodical or for terms and performance that contains a periodication obcurrent are based on Mini-Circust's applicable established test performance criteria and measurement instructions.
The parts covered by this specification document are subject to Mini-Circust standard limited warranty and terms and conditions (collectively, "Standard Terms"): Purchasers of this part are entitled.