Engineering Development Model

Voltage Controlled Oscillator

ROS-EDR9657

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE: CK605

ELECTRICAL SPECIFICATIONS 50Ω				
Parameter	Min.	Тур.	Max.	Units
Frequency	5400		5500	MHz
Tuning Voltage	0.5		14.0	V
Power Output		+2.5		dBm
Phase Noise				
at 1 kHz offset		-71		dBc/Hz
at 10 KHz offset		-96		dBc/Hz
at 100 KHz offset		-117		dBc/Hz
at 1000 kHz offset		-136		dBc/Hz
Pulling at 12 dBr PK-PK all phases		1.3		MHz
Pushing at Vcc=5V±0.25V		4.6		MHz/V
Tuning Sensitivity		28 - 30		MHz/V
Harmonic Suppression		-35	-25	dBc
3 dB Modulation Bandwidth		175000		kHz
Supply Voltage		5		V
Supply Current			35	mA

MAXIMUM RATINGS			
Operating Temperature	-55°C to 85°C		
Storage Temperature	-55°C to 100°C		
Absolute Supply Voltage (Vcc)	+7V		
Absolute Tuning Voltage (Vtune)	+16V		

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be secluded and do not form a part of this specification document.

B. Eschristin pereforations, and performance into conditionance in this consolidation of the specification of the performance in the conditionance in the conditionance in the conditionance in this conditional conditions and making the performance in the conditional conditions and making the performance in the conditional conditions are intended to be secluded as the performance in the conditions are intended to be secluded as the performance in the conditions are intended to be secluded as the performance in the conditions are intended to be secluded as the performance in the conditions are intended to be secluded as the performance in the conditions are intended to be secluded as the performance in the conditions are intended to be secluded as the performance in the conditions are intended to be secluded as the performance in the conditions are intended to be secluded as the performance in the conditions are intended to be secluded to the performance in the conditions are intended to be secluded to the performance in the conditions are intended to be secluded to the performance in the conditions are intended to be secluded to the performance in the perfo

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"): Purchasers of this part are entitled to the legits and brieflits contained therein. For a full statement of the Standard Terms and the excluse rights and remodes thresunder, please with Mini-Circuit's website at www.minicircuits.com/MCL3/contemp.jp.