Engineering Development Model

Voltage Controlled Oscillator

ROS-EDR9676

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE: CK605

| ELECTRICAL SPECIFICATIONS 50Ω | | | | | |
|------------------------------------|------|---------|------|--------|--|
| Parameter | Min. | Тур. | Max. | Units | |
| Frequency | 1000 | | 1500 | MHz | |
| Tuning Voltage | 0.5 | | 20.0 | V | |
| Power Output | | +9.5 | | dBm | |
| Phase Noise | | | | | |
| at 1 kHz offset | | -80 | | dBc/Hz | |
| at 10 KHz offset | | -107 | | dBc/Hz | |
| at 100 KHz offset | | -128 | | dBc/Hz | |
| at 1000 kHz offset | | -148 | | dBc/Hz | |
| Pulling at 12 dBr PK-PK all phases | | 3.7 | | MHz | |
| Pushing at Vcc=10V±0.5V | | 0.9 | | MHz/V | |
| Tuning Sensitivity | | 16 - 36 | | MHz/V | |
| Harmonic Suppression | | -18 | | dBc | |
| 3 dB Modulation Bandwidth | | 130000 | | kHz | |
| Supply Voltage | | 10 | | V | |
| Supply Current | | | 38 | mA | |

| MAXIMUM RATINGS | | | |
|---------------------------------|----------------|--|--|
| Operating Temperature | -55°C to 85°C | | |
| Storage Temperature | -55°C to 100°C | | |
| Absolute Supply Voltage (Vcc) | +12V | | |
| Absolute Tuning Voltage (Vtune) | +22V | | |

| PIN CONNECTIONS | | |
|-----------------|--------------------------------|--|
| RF OUT | 10 | |
| VCC | 14 | |
| V-TUNE | 2 | |
| GROUND | 1,3,4,5,6,7,8,9,11,12,13,15,16 | |

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and means rement instructions.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"): Purchasers of this part are entitled to the legits and brieflits contained therein. For a full statement of the Standard Terms and the excluse rights and remodes thresunder, please with Mini-Circuit's website at www.minicircuits.com/MCL3/contemp.jp.