Engineering Development Model

Voltage Controlled Oscillator

ROS-EDR9745

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE: CK605

ELECTRICAL SPECIFICATIONS 50Ω					
Parameter	Min.	Тур.	Max.	Units	
Frequency	2700		3750	MHz	
Tuning Voltage	0.5		15.0	V	
Power Output		+7		dBm	
Phase Noise					
at 1 kHz offset		-65		dBc/Hz	
at 10 KHz offset		-92		dBc/Hz	
at 100 KHz offset		-115		dBc/Hz	
at 1000 kHz offset		-135		dBc/Hz	
Pulling at 12 dBr PK-PK all phases		1.3		MHz	
Pushing at Vcc=7.5V±0.375V		0.9		MHz/V	
Tuning Sensitivity		75 - 124		MHz/V	
Harmonic Suppression		-22	-10	dBc	
3 dB Modulation Bandwidth		80000		kHz	
Supply Voltage		7.5		V	
Supply Current			50	mA	

MAXIMUM RATINGS			
Operating Temperature	-55°C to 85°C		
Storage Temperature	-55°C to 100°C		
Absolute Supply Voltage (Vcc)	+9.5V		
Absolute Tuning Voltage (Vtune)	+17V		

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	

A. Performance and quality attributes and conditions not expressly stated in this specification document, an intended to be excluded and do not form a part of this operation document.

B. Electrical proceding and negligible proceding the proceding of the proced

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"): Purchasers of this part are entitled to the legits and brieflits contained therein. For a full statement of the Standard Terms and the excluse rights and remodes thresunder, please with Mini-Circuit's website at www.minicircuits.com/MCL3/contemp.jp.