## Engineering Development Model

## **Voltage Controlled Oscillator**

## **Important Note**

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.

Please click "Back", and then click "Contact Us" for Applications support.

## ROS-EDR9774



**CASE STYLE: CK1113** 

ELECTRICAL SPECIFICATIONS 50Ω				
Parameter	Min.	Тур.	Max.	Units
Frequency	1890	S	1890	MHz
Tuning Voltage	0.5		4.5	V
Power Output		+4		dBm
Phase Noise				
at 1 kHz offset	~~~	-87		dBc/Hz
at 10 KHz offset		-116		dBc/Hz
at 100 KHz offset		-135	M.C	dBc/Hz
at 1000 kHz offset		-155		dBc/Hz
Pulling at 12 dBr PK-PK all phases		0.1		MHz
Pushing at Vcc=5V±0.25V		0.005		MHz/V
Tuning Sensitivity		17		MHz/V
Harmonic Suppression		-27	-19	dBc
3 dB Modulation Bandwidth	100	50000		kHz
Supply Voltage		5		V
Supply Current			34	mA

MAXIMUM RATINGS		
Operating Temperature	-55°C to 85°C	
Storage Temperature	-55°C to 100°C	
Absolute Supply Voltage (Vcc)	+6.8V	
Absolute Tuning Voltage (Vtune)	+6.5V	

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	