## Engineering Development Model

## **Voltage Controlled Oscillator**

## ROS-EDR9850/2MP

## **Important Note**

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

**CASE STYLE: CK829** 

ELECTRICAL SPECIFICATIONS 50Ω				
Parameter	Min.	Тур.	Max.	Units
Frequency	1250		2100	MHz
Tuning Voltage	0.5		20.0	V
Power Output		+6.5		dBm
Phase Noise				
at 1 kHz offset		-75		dBc/Hz
at 10 KHz offset		-101		dBc/Hz
at 100 KHz offset		-122		dBc/Hz
at 1000 kHz offset		-143		dBc/Hz
Pulling at 12 dBr PK-PK all phases		2.4		MHz
Pushing at Vcc=8V±0.4V		0.6		MHz/V
Tuning Sensitivity		43-73		MHz/V
Harmonic Suppression		-17		dBc
Supply Voltage		8		V
Supply Current			30	mA

MAXIMUM RATINGS		
Operating Temperature	-45°C to 85°C	
Storage Temperature	-55°C to 100°C	
Absolute Supply Voltage (Vcc)	+10V	
Absolute Tuning Voltage (Vtune)	+22V	

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	