## Engineering Development Model

## **Voltage Controlled Oscillator**

## **ROS-EDR9645/2**

## **Important Note**

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

**CASE STYLE: CK605** 

ELECTRICAL SPECIFICATIONS 50Ω					
Parameter	Min.	Тур.	Max.	Units	
Frequency	1527		1584	MHz	
Tuning Voltage	1		4.5	V	
Power Output		+4		dBm	
Phase Noise					
at 1 kHz offset		-80		dBc/Hz	
at 10 KHz offset		-108		dBc/Hz	
at 100 KHz offset		-130		dBc/Hz	
at 1000 kHz offset		-151		dBc/Hz	
Pulling at 12 dBr PK-PK all phases		0.8		MHz	
Pushing at Vcc=5V±0.25V		0.7		MHz/V	
Tuning Sensitivity		32 - 35		MHz/V	
Harmonic Suppression		-24	-17	dBc	
3 dB Modulation Bandwidth		490000		kHz	
Supply Voltage		5		V	
Supply Current			33	mA	

MAXIMUM RATINGS			
Operating Temperature	-55°C to 85°C		
Storage Temperature	-55°C to 100°C		
Absolute Supply Voltage (Vcc)	+7V		
Absolute Tuning Voltage (Vtune)	+6.5V		

PIN CONNECTIONS		
RF OUT	10	
VCC	14	
V-TUNE	2	
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16	

Notes
A. Performance and qualify attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

140323

B. Electrical apecifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
2. The parts overeid by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"): Purchasers of this part are entitled to the injuries and benefits contained thems. For a full statement of the Standard Terms, and the exclusive rights and remodes thresunder, please with Mini-Circuits' website at www.minicircuits.com/MCLStore-terms.jp;