

Coaxial Low Pass Filter

SLP-2.5+

50Ω DC to 2.5 MHz

Maximum Ratings

Operating Temperature -55°C to +100°C

Storage Temperature -55°C to +100°C

RF Power Input 0.5 W max.

Permanent damage may occur if any of these limits are exceeded.

Features

- Good Attenuation Rate, 1.35 Typ. 20 dB / 3 dB BW Ratio
- Rugged Shielded Case
- Other SLP Models Available with Wide Selection of Cut-Off Frequencies

Applications

- Lab Use
- Test Equipment
- Video Equipment



Generic photo used for illustration purposes only

CASE STYLE: FF99

Connectors	Model
SMA	SLP-2.5+


+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Low Pass Filter Electrical Specifications

PASSBAND (MHz)	fco (MHz) Nom.	STOPBAND (MHz)		VSWR (:1)	
		(loss > 20 dB)	(loss > 40 dB)	Passband Typ.	Stopband Typ.
(loss < 1 dB)	(loss 3 dB)	(loss > 20 dB)	(loss > 40 dB)	Typ.	Typ.
DC-2.5	2.75	3.8-5.0	5.0-200	1.7	18


1 dB compression at +13 dBm input power



typical frequency response



electrical schematic





Outline Dimensions (inch/mm)

B	D	E	WT GRAMS
.70	1.98	.312	42.0
(17.78)	(50.29)	(7.92)	

Typical Performance Data

Frequency (MHz)	Insertion Loss (dB)		Return Loss (dB)	Frequency (MHz)	Group Delay (nsec)
	\bar{x}	σ			
0.10	0.06	0.00	33.53	1.00	321.99
0.40	0.08	0.01	23.85	1.06	323.09
0.80	0.10	0.01	25.18	1.12	327.26
1.10	0.12	0.00	32.02	1.18	330.19
1.40	0.17	0.01	21.06	1.25	332.28
1.80	0.24	0.01	18.34	1.32	334.96
2.10	0.28	0.04	21.26	1.40	338.56
2.50	0.45	0.07	18.25	1.48	341.36
2.75	1.34	0.45	9.00	1.56	346.34
3.00	5.99	1.21	2.08	1.65	352.96
3.20	11.74	1.32	0.71	1.74	360.97
3.30	14.61	1.31	0.48	1.84	372.10
3.50	19.96	1.23	0.29	1.94	385.34
3.60	22.44	1.20	0.25	2.05	402.77
3.80	27.02	1.14	0.19	2.17	422.48
4.00	31.16	1.09	0.17	2.29	449.68
4.20	34.94	1.06	0.15	2.42	492.19
4.40	38.42	1.03	0.14	2.50	530.37
4.60	41.65	1.00	0.12	2.75	689.14
4.80	44.65	0.98	0.12	2.86	697.89
5.00	47.46	0.98	0.11	3.02	582.03
5.20	50.11	0.99	0.10	3.19	410.17
29.60	89.73	3.84	0.19	3.37	280.46
53.90	87.32	1.38	0.43	3.56	201.19
78.30	89.67	4.26	0.48	3.80	145.71
102.60	86.70	3.08	0.49	3.98	119.20
127.00	88.19	4.27	0.49	4.20	96.41
151.30	90.79	3.34	0.48	4.44	79.41
175.70	90.31	4.10	0.48	4.74	65.38
200.00	93.47	9.35	0.47	5.01	55.83



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

