

Engineering Development Model

Frequency Synthesizer

TSN-EDR10936/2

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

CASE STYLE : 99-01-1777

ELECTRICAL SPECIFICATIONS 50Ω, over -45°C to +85°C				
Parameter	Min.	Typ.	Max.	Units
Frequency	2250		2560	MHz
Step size		10000		kHz
Settling Time Within ±1kHz		480		μsec
Output Power	+9	+13	+17	dBm
Phase Noise				
at 100 Hz offset		-87		dBc/Hz
at 1 kHz offset		-96		dBc/Hz
at 10 KHz offset		-97		dBc/Hz
at 100 KHz offset		-120		dBc/Hz
at 1000 kHz offset		-145	-139	dBc/Hz
Integrated SSB Phase Noise		-53		dBc
Ref & Comp Spurious Suppression		104		dBc
Non-Harm. Spurious Suppression		-90		dBc
Harmonic Suppression		-30		dBc
Supply voltage	VCO	5		V
	PLL	3		V
Supply current	VCO	57	68	mA
	PLL	11	19	mA
Reference In (External)	Frequency	10		MHz
	Amplitude	1		Vp-p
	Impedance	100		kΩ
	Ph. N @ 1kHz	-145		dBc/Hz
Input Logic Levels	Logic high	1.4	3	V
	Logic Low		0.6	V
Digital Lock Detect	Locked	2.6	3	V
	Unlocked		0.4	V
Frequency Synthesizer PLL	ADF4106			

ABSOLUTE MAXIMUM RATINGS

Operating Temperature	-45°C to 85°C
Storage Temperature	-55°C to 100°C
VCO Supply Voltage	6V
PLL Supply Voltage	4V
Reference Frequency voltage	3.6Vp-p
Data, Clock & LE levels	3.3V

Power On sequence: Vcc VCO followed by Vcc PLL

Power Off sequence: Vcc PLL followed by Vcc VCO

PIN CONNECTIONS

RF OUT	13	CLOCK	2
VCC VCO	14	DATA	3
VCC PLL	15	LOAD ENABLE	4
REF IN	16	GROUND	6-12,17-22
LOCK DETECT	1		

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"). Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp

