

Engineering Development Model

Voltage Controlled Oscillator

UOS-EDR5477/2

Important Note

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



CASE STYLE : CZ682

Please click "Back", and then click "Contact Us" for Applications support.

ELECTRICAL SPECIFICATIONS 50Ω				
Parameter	Min.	Typ.	Max.	Units
Frequency	1642		1795	MHz
Tuning Voltage	0.5		7	V
Power Output		+1		dBm
Phase Noise				
at 1 kHz offset		-72		dBc/Hz
at 10 KHz offset		-100		dBc/Hz
at 100 KHz offset		-125		dBc/Hz
at 1000 kHz offset		-144		dBc/Hz
Pulling at 12 dBm PK-PK all phases		3.1		MHz
Pushing at Vcc=5V±0.25V		1.25		MHz/V
Tuning Sensitivity		27 - 40		MHz/V
Harmonic Suppression		-30	-23	dBc
3 dB Modulation Bandwidth		7400		kHz
Supply Voltage		5.7		V
Supply Current			30	mA

MAXIMUM RATINGS	
Operating Temperature	-55°C to 85°C
Storage Temperature	-55°C to 100°C
Absolute Supply Voltage (Vcc)	+7.7V
Absolute Tuning Voltage (Vtune)	+9V

PIN CONNECTIONS	
RF OUT	10
VCC	14
V-TUNE	1
GROUND	2,4,6,7,8