50Ω

SMA Fixed Attenuator

12dB

VAT-12+

Generic photo used for illustration purposes only

CASE STYLE: FF704

SMA VAT-12+

Connectors Model

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Maximum Ratings

Operating Temperature -45°C to 100°C Storage Temperature -55°C to 100°C

1W

Permanent damage may occur if any of these limits are exceeded

Outline Drawing



Outline Dimensions (inch)

В D Ε wt .410 .312 grams 1.43 10.41 36.32 7.92 10.0

Features

- wideband coverage, DC to 6000 MHz
- 1 watt rating
- rugged unibody construction

DC to 6000 MHz

- · off-the-shelf availability
- · very low cost

Applications

- impedance matching
- · signal level adjustment

Electrical Specifications


FREQ. RANGE (MHz)	ATTENUATION * (dB) Flatness **				VSWR (:1)			MAX. INPUT POWER	
		DC-3 GHz	3-5 GHz	5-6 GHz	DC-6 GHz	DC-3 GHz	3-5 GHz	5-6 GHz	(W)
f _L f _U	Nom.	Тур.	Тур.	Тур.	Тур.	Тур. Мах.	Тур. Мах.	Тур.	
DC-6000	12±0.3	0.10	0.10	0.10	0.30	1.05 1.35	1.20 1.70	1.65	1.0


Attenuation varies by 0.3 dB max. over temperature.


Typical Performance Data

Frequency (MHz)	Attenuation (dB)	VSWR (:1)
0.03	11.96	1.03
50.00	11.99	1.02
100.00	11.99	1.01
500.00	12.10	1.01
1000.00	12.13	1.03
2000.00	12.11	1.10
3000.00	12.05	1.23
4000.00	11.92	1.28
5000.00	11.79	1.38
6000.00	11.84	1.61

Electrical Schematic







A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively: "Standard Terms"): Purchases of this part. Ferrormance and updany authorities and contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

^{**} Flatness= variation over band divided by 2.