## Engineering Development Model

## Power Splitter/Combiner ZB4PD-ED14430/1

4 Way-0°

## **Important Note**

This model has been designed, built and tested in our engineering department. Performance data represents model capability. At present it is a non-catalog model. On request, we can supply a final specification sheet, part number and price/delivery information.



Please click "Back", and then click "Contact Us" for Applications support.

**CASE STYLE: UU182** 

ELECTRICAL SPECIFICATIONS 50Ω @ +25°C					
Parameter		Min.	Тур.	Max.	Units
Frequency		600		2600	MHz
Isolation	600-2600 MHz		20		dB
	800-2400 MHz		24		dB
Insertion Loss Above 6.0 dB	600-2600 MHz		0.90		dB
Phase Unbalance	600-2600 MHz		1.50		deg.
Amplitude Unbalance	600-2600 MHz		0.20		dB
VSWR	SUM Port		1.38		(:1)
	OUT Ports		1.25		(:1)

MAXIMUM RATINGS			
Operating Temperature	-55°C to 100°C		
Storage Temperature	-55°C to 100°C		

COAXIAL CONNECTIONS			
SUM PORT	S		
PORT 1	1		
PORT 2	2		
PORT 3	3		
PORT 4	4		

## **Functional Diagram**



