



COAXIAL

Medium High Power Amplifier

ZHL-2-S+ ZHL-2X-S+

50Ω 10 to 1000 MHz

FEATURES

- Wideband, 10 to 1000 MHz
- High IP3, +42 dBm typ.
- Medium High Power, 28 dB min.



Generic photo used for illustration purposes only

APPLICATIONS

- VHF/UHF
- Cellular
- Instrumentation
- Laboratory

Model No.	ZHL-2-S+	ZHL-2X-S+ [▲]
Case Style	T34	
Connectors	SMA	

+RoHS Compliant
The +Suffix identifies RoHS Compliance.
See our website for methodologies and qualifications

ELECTRICAL SPECIFICATIONS AT 25°C

Parameter	Condition (MHz)	ZHL-2-S+ ZHL-2X-S+ [▲]			Units
		Min.	Typ.	Max.	
Frequency Range		10	—	1000	MHz
Gain	10-1000	16	20	24	dB
Gain Flatness	10-1000	—	±0.9	±1.4	dB
Output Power at 1dB compression	10-1000	+28	+29	—	dBm
Output Power at 3dB compression	10-1000	+29	+30	—	dBm
Noise Figure	10-1000	—	9.0	—	dB
Output third order intercept point	10-1000	—	+42	—	dBm
Input VSWR	10-1000	—	—	2.0	:1
Output VSWR	10-1000	—	—	2.1	:1
DC Supply Voltage		—	24	—	V
Supply Current		—	—	0.6	A

Open load is not recommended, potentially can cause damage.
With no load derate max. input power by 20 dB.

[▲] Heat sink not included. Alternative heat sinking and heat removal must be provided by the user to limit maximum base-plate temperature to 65°C, in order to ensure proper performance. For reference, this requires thermal resistance of user's external heat sink to be 1.35°C/W max.

ABSOLUTE MAXIMUM RATINGS

Parameter	Ratings
Operating Temperature	-20°C to +65°C
Storage Temperature	-55°C to +100°C
DC Voltage	+25V
Input RF Power (no damage)	+15 dBm

Permanent damage may occur if any of these limits are exceeded.





COAXIAL


Medium High Power Amplifier

ZHL-2-S+ ZHL-2X-S+


Mini-Circuits

50Ω 10 to 1000 MHz

OUTLINE DRAWING FOR MODELS WITH HEATSINK



MOUNTING INFORMATION FOR MODELS WITHOUT HEATSINK



OUTLINE DIMENSIONS (Inch/mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	wt
4.75	2.00	2.12	.19	4.375	.23	1.540	.144	.58	.34	.50	1.50	1.00	.12	.38	4.00	.30	2.60	grams*
120.65	50.80	53.85	4.83	111.13	5.84	39.12	3.66	14.73	8.64	12.70	38.10	25.40	3.05	9.65	101.60	7.62	66.04	440.0
																		*325 grams without heatsink



COAXIAL

Medium High Power Amplifier







ZHL-2-S+ ZHL-2X-S+

Mini-Circuits

50Ω 10 to 1000 MHz

TYPICAL PERFORMANCE DATA/CURVES

FREQUENCY (MHz)	GAIN (dB)	DIRECTIVITY (dB)	VSWR (:1)		POUT at 1 dB COMPR. (dBm)	NOISE FIGURE (dB)	IP3 (dBm)
	24V	24V	IN	OUT	24V	24V	24V
10.00	20.45	32.57	1.05	1.82	29.87	9.39	45.49
50.00	20.85	32.00	1.06	1.82	30.41	8.73	46.62
100.00	20.76	32.18	1.04	1.68	30.63	8.71	46.40
200.00	20.37	32.96	1.06	1.34	30.75	8.73	44.96
250.00	20.18	33.30	1.11	1.19	30.78	8.68	44.62
300.00	20.06	33.43	1.17	1.07	30.78	8.60	44.23
350.00	20.01	33.72	1.24	1.06	30.70	8.63	43.79
400.00	20.06	33.73	1.31	1.15	30.80	8.64	43.74
500.00	20.48	32.96	1.42	1.34	30.67	8.60	43.93
600.00	21.10	31.54	1.45	1.49	30.75	8.64	45.66
650.00	21.31	31.09	1.41	1.53	30.71	8.66	45.08
700.00	21.37	30.96	1.36	1.54	30.91	8.55	44.42
800.00	20.91	31.92	1.33	1.47	30.56	8.59	43.61
900.00	20.12	33.79	1.50	1.37	30.62	8.62	42.63
1000.00	19.76	34.78	1.70	1.35	29.81	8.62	41.66



NOTES

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the standard terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/terms/viewterm.html

