

Coaxial

Power Splitter/Combiner

ZSC-2-2-75+

2 Way-0° 75Ω 0.002 to 60 MHz



CASE STYLE: M22

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	1W max.
Internal Dissipation	0.125W max.


At low range frequency band (f_L to $10 f_L$), linearly derate maximum input power by 13 dB.

Permanent damage may occur if any of these limits are exceeded.

Coaxial Connections

SUM PORT	2
PORT 1	1
PORT 2	3

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H
2.25	1.38	1.24	.50	.150	3.100	.138	1.238
57.15	35.05	31.50	12.70	3.81	78.74	3.51	31.45

J	K	L	M	N	P	S	wt
3.25	.10	.40	1.15	1.86	.64	.150	grams
82.55	2.54	10.16	29.21	47.24	16.26	3.81	74.0

Features

- low insertion loss, 0.3 dB typ.
- high isolation, 30 dB typ.
- excellent amplitude unbalance, 0.1 dB typ.
- excellent phase unbalance, 0.2 deg. typ.
- rugged shielded case

Applications

- HF
- amateur radio

Electrical Specifications




FREQ. RANGE (MHz)	ISOLATION* (dB)						INSERTION LOSS* (dB) ABOVE 3.0 dB						PHASE UNBALANCE (Degrees)			AMPLITUDE UNBALANCE (dB)		
	L		M		U		L		M		U		L		M		U	
	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Max.	Max.	Max.	Max.	Max.	Max.

L = low range [f_L to $10 f_L$] M = mid range [$10 f_L$ to $f_U/2$] U = upper range [$f_U/2$ to f_U]


* Isolation specified to -20°C from 0.002 to 0.004 MHz. From 0.002 to 0.006 MHz, isolation 14 dB min.

Typical Performance Data

Frequency (MHz)	Insertion Loss (dB)		Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1	S-2						
0.002	3.18	3.18	0.00	24.51	0.08	1.21	1.37	1.37
0.510	3.07	3.07	0.00	64.03	0.00	1.02	1.00	1.00
1.000	3.07	3.07	0.00	55.50	0.00	1.02	1.00	1.00
10.000	3.16	3.15	0.00	38.79	0.00	1.05	1.06	1.06
13.000	3.18	3.18	0.00	37.41	0.00	1.06	1.08	1.08
15.000	3.19	3.19	0.00	36.66	0.01	1.07	1.09	1.09
17.000	3.20	3.20	0.00	36.00	0.01	1.09	1.11	1.11
30.000	3.30	3.30	0.00	32.49	0.01	1.16	1.20	1.20
34.000	3.33	3.33	0.00	31.45	0.01	1.19	1.23	1.23
38.000	3.36	3.36	0.00	30.37	0.00	1.22	1.27	1.27
42.000	3.40	3.40	0.00	29.26	0.00	1.25	1.30	1.30
48.000	3.45	3.45	0.00	27.58	0.00	1.29	1.35	1.35
54.000	3.50	3.51	0.01	25.91	0.01	1.34	1.40	1.40
58.000	3.55	3.55	0.01	24.84	0.02	1.37	1.43	1.44
60.000	3.57	3.58	0.01	24.31	0.02	1.38	1.45	1.45



electrical schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

For detailed performance specs
& shopping online see web site

REV. B
M120055
ZSC-2-2-75+
HY/TD/CP/AM
090824