



Mini-Circuits

ULTRA LOW NOISE, MEDIUM CURRENT

D-PHEMT Transistor

SAV-331+

50Ω 10-4000 MHz

THE BIG DEAL

- Low Noise Figure, 0.5 dB typ. at 300 MHz
- Gain, 24.1 dB typ. at 300 MHz
- High Output IP3, +32.3 dBm typ. at 300 MHz
- Output Power at 1dB comp., +19.6 dBm typ. at 300 MHz
- Low Current, 60mA
- External biasing and matching required



Generic photo used for illustration purposes only

CASE STYLE: MMM1362

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications



APPLICATIONS

- Cellular
- ISM
- GSM
- WCDMA
- WiMax
- WLAN
- UNII and HIPERLAN

PRODUCT OVERVIEW

Mini-Circuits' SAV-331+ is a MMIC D-PHEMT transistor with an operating frequency range from 10 to 4000 MHz. This model combines high gain with extremely low noise figure, resulting in lower overall system noise. Low NF and IP3 performance make it an ideal choice for sensitive receivers in communications systems. Manufactured using highly repeatable D-PHEMT* technology, the unit comes housed in a tiny 4-lead SOT-343 package. This model requires external biasing and matching.

SIMPLIFIED SCHEMATIC AND PIN DESCRIPTION



Function	Pin Number	Description
Source	2 & 4	Source terminal, normally connected to ground
Gate	3	Gate used for RF Input
Drain	1	Drain used for RF output

* Depletion mode Pseudomorphic High Electron Mobility Transistor.

REV. B
ECO-010314
SAV-331+
RS/CP/AM
211022





Mini-Circuits®

ULTRA LOW NOISE, MEDIUM CURRENT

D-PHEMT Transistor

SAV-331+

ELECTRICAL SPECIFICATIONS AT $T_{AMB}=25^{\circ}\text{C}$, FREQUENCY 10 TO 4000 MHZ

Symbol	Parameter	Condition	Min.	Typ.	Max.	Units
DC Specifications						
V_{GS}	Operational Gate Voltage	$V_{DS}=4\text{V}$, $I_{DS}=60\text{ mA}$	-0.96	-0.69	-0.51	V
V_P	Pinch-off Voltage	$V_{DS}=1.5\text{ V}$, $I_{DS}=10\%$ of I_{DSS}		-0.81		V
I_{DSS}	Saturated Drain Current	$V_{DS}=4\text{V}$, $V_{GS}=0\text{ V}$		228		μA
G_M	Transconductance	$V_{DS}=4\text{V}$, $G_m=\Delta I_{DS}/\Delta V_P$	—	—	—	mS
			—	282	—	
			—	—	—	
			—	—	—	
I_{GDO}	Gate to Drain Leakage Current	$V_{GD}=5\text{V}$			1000	μA
I_{GSS}	Gate leakage Current	$V_{GD}=V_{GS}=-4\text{V}$			600	μA
Specifications, $Z_0=50\text{ Ohms}$ (Figure 1)*						
NF	Noise Figure	$V_{DS}=4\text{V}$, $I_{DS}=60\text{ mA}$		0.9		dB
		$f=40\text{ MHz}$		0.5		
		$f=300\text{ MHz}$		0.4		
		$f=900\text{ MHz}$		0.5	0.8	
		$f=2000\text{ MHz}$		0.5		
		$f=4000\text{ MHz}$		0.9		
Gain	Gain	$V_{DS}=4\text{V}$, $I_{DS}=60\text{ mA}$		24.6		dB
		$f=40\text{ MHz}$		24.1		
		$f=300\text{ MHz}$		21.3		
		$f=900\text{ MHz}$	13.9	16.6	18.3	
		$f=2000\text{ MHz}$		11.5		
		$f=4000\text{ MHz}$				
OIP3	Output IP3	$V_{DS}=4\text{V}$, $I_{DS}=60\text{ mA}$		30.9		dBm
		$f=40\text{ MHz}$		32.3		
		$f=300\text{ MHz}$		33.5		
		$f=900\text{ MHz}$		35.5		
		$f=2000\text{ MHz}$		38.7		
		$f=4000\text{ MHz}$				
P1dB	Power output at 1 dB Compression	$V_{DS}=4\text{V}$, $I_{DS}=60\text{ mA}$		19.1		dBm
		$f=40\text{ MHz}$		19.6		
		$f=300\text{ MHz}$	18.0	20.2		
		$f=900\text{ MHz}$	18.9	21.1		
		$f=2000\text{ MHz}$		21.8		
		$f=4000\text{ MHz}$				
Θ_{JC}	Thermal Resistance			109		$^{\circ}\text{C/W}$

* Tested on Mini-Circuits TB-471+ test board

MAXIMUM RATINGS⁽¹⁾

Symbol	Parameter	Max.	Units
V_{DS}	Drain-Source Voltage ²	5	V
V_{GS}	Gate-Source Voltage ²	-5	V
V_{GD}	Gate-Drain Voltage ²	-5	V
I_{DS}	Drain Current ²	149	mA
P_{DISS}	Total Dissipated Power	400	mW
P_{IN}	RF Input Power	20	dBm
T_{CH}	Channel Temperature	150	$^{\circ}\text{C}$
T_{OP}	Operating Temperature	-40 to 85	$^{\circ}\text{C}$
T_{STD}	Storage Temperature	-65 to 150	$^{\circ}\text{C}$

(1) Operation of this device above any one of these parameters may cause permanent damage.

(2) Assumes DC quiescent conditions, $V_{GS} = -0.51\text{ V}$, $V_{DS} = 4\text{ V}$.



Mini-Circuits

ULTRA LOW NOISE, MEDIUM CURRENT

D-PHEMT Transistor

SAV-331+

CHARACTERIZATION TEST CIRCUIT




Fig 1. Block Diagram of Test Circuit used for characterization. (DUT soldered on Mini-Circuits Test Board TB-471+)

Gain, Output power at 1dB compression (P1 dB) and output IP3 (OIP3) are measured using R&S Network Analyzer ZVA-24. Noise Figure measured using keysight PNA-X.

Conditions:

1. Drain voltage (with reference to source, V_{DS}) = 4V as shown.
2. Gate Voltage (with reference to source, V_{GS}) is set to obtain desired Drain-Source current (I_{DS}) as shown in graphs or specification table.
3. Gain: $P_{in} = -25\text{dBm}$
4. Output IP3 (OIP3): Two tones, spaced 1 MHz apart, 0 dBm/tone at output.
5. No external matching components used.





Fig 2. Test Board used for characterization, Mini-Circuits P/N TB-471+ (Material: Rogers 4350, Thickness: 0.02")

PRODUCT MARKING



Mini-Circuits



ADDITIONAL DETAILED TECHNICAL INFORMATION IS AVAILABLE ON OUR DASH BOARD. TO ACCESS [CLICK HERE](#)

Performance Data	Data Table
	Swept Graphs
	S-Parameter (S2P Files) Data Set (.zip file)
Case Style	MMM1362 Plastic molded SOT-343 (SC-70) style package, lead finish: matte-tin
Tape & Reel Standard quantities available on reel	F90 7" reels with 20, 50, 100, 200, 500, 1K, 2K or 3K devices
Suggested Layout for PCB Design	PL-300
Evaluation Board	TB-471+
Environmental Ratings	ENV08T2


ESD RATING

Human Body Model (HBM): Class 0 (<250V) in accordance with ANSI/ESD STM 5.1 - 2001

Machine Model (MM): Class M1 (40 V) in accordance with ANSI/ESD STM 5.2 - 1999

MSL RATING

Moisture Sensitivity: MSL1 in accordance with IPC/JEDEC J-STD-020D

MSL TEST FLOW CHART**NOTES**

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the standard. Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

Typical Performance Data

VDS (V)	IDS ⁽²⁾ (mA)						
	@ VGS=						
	-1.00V	-0.90V	-0.8V	-0.7V	-0.6V	-0.4V	-0.2V
0.00	-0.01	-0.01	0.03	0.04	-0.01	-0.12	-0.14
0.10	1.32	3.19	8.04	14.00	19.61	28.89	34.79
0.20	1.67	4.87	12.63	23.34	34.52	54.04	67.14
0.30	1.85	5.85	15.15	28.87	44.46	74.08	95.598
0.40	1.98	6.53	16.73	32.10	50.52	88.67	120.14
0.50	2.11	7.05	17.86	34.12	54.08	98.28	138.3
0.60	2.22	7.46	18.72	35.53	56.26	104.20	150.94
0.70	2.32	7.79	19.41	36.62	57.79	107.32	158.6
0.80	2.43	8.09	20.01	37.56	59.04	109.22	162.68
0.90	2.52	8.37	20.56	38.39	60.11	110.60	164.94
1.00	2.62	8.63	21.08	39.15	61.07	111.72	166.36
1.10	2.71	8.88	21.56	39.86	61.95	112.68	167.34
1.20	2.80	9.12	22.02	40.53	62.78	113.52	168.08
1.30	2.89	9.36	22.45	41.16	63.55	114.24	168.62
1.40	2.98	9.59	22.87	41.77	64.27	114.88	169.04
1.50	3.06	9.82	23.30	42.35	64.97	115.48	169.34
1.60	3.15	10.07	23.75	42.95	65.64	116.02	169.62
1.70	3.25	10.36	24.27	43.58	66.30	116.52	169.84
1.80	3.37	10.73	24.89	44.31	66.96	117.02	170.00
1.90	3.52	11.20	25.67	45.16	67.66	117.48	170.18
2.00	3.69	11.79	26.61	46.04	68.36	117.92	170.30
2.10	3.88	12.50	27.60	46.97	69.08	118.32	170.26
2.20	4.10	13.07	28.39	47.86	69.78	118.72	170.18
2.30	4.29	13.50	29.01	48.62	70.41	119.12	170.18
2.40	4.45	13.85	29.51	49.24	71.02	119.50	170.26
2.50	4.58	14.15	29.93	49.77	71.57	119.84	170.46
2.60	4.70	14.40	30.28	50.22	72.06	120.24	170.70
2.70	4.81	14.63	30.62	50.62	72.51	120.56	171.12
2.80	4.90	14.82	30.90	50.98	72.92	120.90	171.26
2.90	4.98	15.01	31.17	51.30	73.30	121.20	171.42
3.00	5.07	15.19	31.42	51.61	73.65	121.50	171.60
3.10	5.15	15.35	31.65	51.88	73.98	121.82	171.80
3.20	5.22	15.50	31.86	52.16	74.28	122.16	171.98
3.30	5.30	15.65	32.08	52.41	74.57	122.46	172.14
3.40	5.37	15.80	32.27	52.65	74.85	122.84	172.28
3.50	5.44	15.93	32.47	52.88	75.12	123.20	--
3.60	5.51	16.06	32.65	53.11	75.39	123.58	--
3.70	5.57	16.19	32.83	53.33	75.65	123.96	--
3.80	5.64	16.32	33.00	53.53	75.90	124.32	--
3.90	5.70	16.44	33.17	53.74	76.17	124.68	--
4.00	5.77	16.56	33.34	53.95	76.42	125.04	--
4.10	5.83	16.68	33.50	54.16	76.69	125.36	--
4.20	5.90	16.80	33.68	54.36	76.96	125.68	--
4.30	5.97	16.92	33.84	54.56	77.23	125.96	--
4.40	6.03	17.04	34.00	54.77	77.52	126.28	--
4.50	6.10	17.16	34.17	54.98	77.80	126.54	--
4.60	6.16	17.28	34.33	55.19	78.10	126.74	--
4.70	6.23	17.39	34.50	55.41	78.41	127.00	--
4.80	6.30	17.51	34.67	55.63	78.71	--	--
4.90	6.37	17.64	34.84	55.86	79.03	--	--
5.00	6.44	17.76	35.01	56.09	79.35	--	--

Typical Performance Data

FREQ (GHz)	GAIN vs FREQ & TEMPERATURE ⁽¹⁾ @ VDS=4V, IDS=60mA			NOISE FIGURE vs FREQ & TEMPERATURE ⁽¹⁾ @ VDS=4V, IDS=60mA		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
0.01	24.87	24.53	24.13	2.76	4.40	5.38
0.05	24.81	24.49	24.09	0.54	0.78	1.08
0.10	24.78	24.47	24.07	0.40	0.48	0.65
0.20	24.60	24.28	23.90	0.39	0.46	0.57
0.30	24.34	24.01	23.63	0.45	0.52	0.62
0.40	24.00	23.66	23.26	0.29	0.36	0.46
0.50	23.59	23.24	22.84	0.38	0.45	0.55
0.60	23.15	22.79	22.40	0.35	0.42	0.52
0.70	22.67	22.30	21.92	0.31	0.40	0.49
0.80	22.17	21.81	21.44	0.39	0.45	0.57
0.90	21.68	21.31	20.94	0.31	0.40	0.52
1.00	21.18	20.82	20.46	0.32	0.42	0.52
1.10	20.69	20.33	19.98	0.35	0.46	0.56
1.20	20.21	19.85	19.51	0.36	0.46	0.56
1.30	19.74	19.38	19.06	0.40	0.48	0.61
1.40	19.29	18.93	18.62	0.41	0.52	0.65
1.50	18.85	18.50	18.19	0.38	0.49	0.61
1.60	18.44	18.09	17.79	0.36	0.47	0.61
1.70	18.04	17.69	17.39	0.39	0.50	0.64
1.80	17.66	17.31	17.02	0.37	0.51	0.65
1.90	17.29	16.94	16.65	0.42	0.55	0.70
2.00	16.94	16.59	16.31	0.35	0.49	0.62
2.10	16.61	16.26	15.97	0.37	0.51	0.64
2.20	16.29	15.94	15.65	0.37	0.51	0.65
2.30	15.98	15.62	15.33	0.34	0.50	0.66
2.40	15.68	15.32	15.03	0.39	0.54	0.72
2.50	15.39	15.03	14.74	0.44	0.70	0.78
2.60	15.12	14.76	14.46	0.46	0.62	0.81
2.70	14.86	14.49	14.19	0.52	0.67	0.87
2.80	14.60	14.23	13.93	0.54	0.74	0.91
2.90	14.34	13.97	13.66	0.55	0.73	0.90
3.00	14.10	13.73	13.42	0.51	0.68	0.86
3.10	13.86	13.48	13.17	0.51	0.71	0.89
3.20	13.62	13.24	12.92	0.55	0.73	0.94
3.30	13.39	13.01	12.69	0.53	0.72	0.94
3.40	13.17	12.79	12.47	0.51	0.73	0.95
3.50	12.94	12.56	12.24	0.55	0.78	0.99
3.60	12.72	12.34	12.01	0.54	0.78	1.00
3.70	12.50	12.12	11.79	0.58	0.82	1.02
3.80	12.28	11.90	11.57	0.62	0.84	1.08
3.90	12.06	11.68	11.35	0.61	0.85	1.11
4.00	11.85	11.47	11.14	0.65	0.89	1.15






⁽¹⁾ Includes test board loss⁽²⁾ Drain current was allowed to increase during compression measurement

Typical Performance Data

FREQ (GHz)	OIP3 vs FREQ & TEMPERATURE ⁽¹⁾ @ VDS=4V, IDS=60mA			P1dB vs FREQ & TEMPERATURE ^(1,2) @ VDS=4V, IDS=60mA		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
0.01	31.39	30.90	30.00	18.42	19.24	19.17
0.05	31.86	32.06	31.61	18.56	19.39	19.67
0.10	32.32	32.33	31.65	18.73	19.53	19.65
0.20	32.25	32.28	31.63	18.97	19.63	19.74
0.30	32.13	32.08	31.69	18.91	19.90	20.00
0.40	32.26	32.19	31.73	19.02	19.96	19.93
0.50	32.94	32.93	32.04	19.06	19.78	19.75
0.60	32.47	32.80	32.05	19.37	20.11	20.21
0.70	32.86	33.08	32.51	19.34	20.05	20.04
0.80	32.90	33.10	32.54	19.63	20.28	20.26
0.90	33.30	33.59	32.83	19.69	20.37	20.38
1.00	33.36	33.72	32.97	19.83	20.50	20.50
1.10	33.14	33.48	32.81	20.06	20.59	20.72
1.20	32.97	33.47	32.91	20.19	20.71	20.73
1.30	34.17	34.30	33.31	20.21	20.57	20.58
1.40	33.46	34.29	33.08	20.34	20.82	20.84
1.50	33.62	34.21	33.42	20.47	20.84	20.88
1.60	34.17	34.58	33.44	20.35	20.79	20.82
1.70	34.93	35.40	34.55	20.25	20.55	20.58
1.80	35.17	35.87	34.99	20.57	21.01	21.03
1.90	34.45	34.68	34.15	20.66	21.10	21.13
2.00	35.02	35.53	34.74	20.78	21.20	21.12
2.10	35.03	35.48	34.81	20.76	21.20	21.13
2.20	34.84	35.97	35.35	20.69	21.08	21.00
2.30	35.79	36.16	35.23	20.83	21.10	21.13
2.40	35.80	36.55	35.53	20.79	21.04	20.95
2.50	35.69	36.72	35.15	21.13	21.39	21.31
2.60	35.03	36.38	35.75	21.06	21.31	21.33
2.70	34.83	34.99	35.93	21.09	21.43	21.33
2.80	36.19	37.30	35.44	21.17	21.39	21.29
2.90	35.90	36.82	36.31	21.10	21.31	21.21
3.00	36.03	37.01	36.34	21.15	21.38	21.37
3.10	35.97	36.99	36.43	21.44	21.65	21.53
3.20	36.05	37.26	36.47	21.44	21.68	21.56
3.30	36.53	37.82	37.48	21.13	21.33	21.32
3.40	36.21	38.21	36.68	21.45	21.55	21.54
3.50	36.01	37.74	36.87	21.51	21.73	21.72
3.60	36.13	38.09	37.49	21.11	21.20	21.19
3.70	35.62	37.64	36.84	21.36	21.57	21.46
3.80	36.57	38.41	37.49	21.46	21.55	21.54
3.90	36.74	38.97	37.86	21.39	21.60	21.49
4.00	36.87	38.97	37.43	21.62	21.71	21.71

⁽¹⁾ Includes test board loss⁽²⁾ Drain current was allowed to increase during compression measurement


Typical Performance Curves




⁽¹⁾ Includes test board loss

⁽²⁾ Drain current was allowed to increase during compression measurement

Outline Dimensions



PCB Land Pattern



Suggested Layout,
Tolerance to be within $\pm .002$

CASE #.	A	B	C	D	E	F	G	H	J	K	L	M	N	P
MMM1362	.045 (1.15)	.053 (1.35)	.073 (1.85)	.089 (2.25)	.043 (1.10)	.004 (0.10)	.071 (1.80)	.094 (2.40)	.046 (1.17)	.056 (1.43)	- -	- -	.022 (0.55)	.028 (0.70)

CASE #.	Q	R	S	T	WT, GRAM
MMM1362	.010 (0.25)	.016 (0.40)	.017 (0.43)	.006 (0.15)	.007

Dimensions are in inches (mm). Tolerances: 2 Pl. $\pm .01$; 3 Pl. $\pm .005$

Notes:

- Case material: Plastic.
- Termination finish:
For RoHS Case Styles: Matte Tin plate.



INTERNET <http://www.minicircuits.com>


P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified

Tape & Reel Packaging TR-F90

DEVICE ORIENTATION IN T&R



Applicable Case Style
MMM1362

NONE

Tape Width, mm	Device Cavity Pitch, mm	Reel Size, inches	Devices per Reel	
8	4	7	Small quantity standards (see note)	20
				50
				100
				200
				500
				1000
		7	Standards	2000
				3000

Note: Please Consult individual model data sheet to determine device per reel availability.

| [Applicable Case Styles](#) |

Mini-Circuits carrier tape materials provide protection from ESD (Electro-Static Discharge) during handling and transportation. Tapes are static dissipative and comply with industry standards EIA-481/EIA-541.

Go to: www.minicircuits.com/pages/pdfs/tape.pdf

| [MZ4532C](#) |




Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified

INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661


THIRD ANGLE PROJECTION




REVISIONS

REV	ECN No.	DESCRIPTION	DATE	DR	AUTH
OR	M121884	NEW RELEASE	03/10/09	AV	TH

SUGGESTED MOUNTING CONFIGURATION FOR MMM1362 CASE STYLE, "04AM02" PIN CODE



NOTES:

1. TRACE WIDTH IS SHOWN FOR REFERENCE ONLY. ACTUAL LINE WIDTH IS A FUNCTION OF SPECIFIC MATCHING CIRCUIT.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
3.  DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER);
 DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK.

UNLESS OTHERWISE SPECIFIED

INITIALS

DATE

DIMENSIONS ARE IN INCHES

TOLERANCES ON:
2 PL DECIMALS ±
3 PL DECIMALS ± .005
ANGLES ±
FRACTIONS ±

DRAWN

AV

03/09/09

CHECKED

IL

03/10/09

APPROVED

TH

03/10/09

 Mini-Circuits®

THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF MINI-CIRCUITS. EXCEPT FOR USE EXPRESSLY GRANTED, IN WRITING, TO ITS VENDORS, VENDEE AND THE UNITED STATES GOVERNMENT, MINI-CIRCUITS RESERVES ALL PROPRIETARY DESIGN, USE, MANUFACTURING AND REPRODUCTION RIGHTS THERETO. THESE CONTENTS SHALL NOT BE USED, DUPLICATED OR DISCLOSED TO ANY OUTSIDE PARTY, IN WHOLE OR IN PART, WITHOUT WRITTEN PERMISSION OF MINI-CIRCUITS.

ASHEETA1.DWG REV:A DATE:01/12/95



Mini-Circuits®

 13 Neptune Avenue
Brooklyn NY 11235

PL, 04AM02, FG873, SAV

 SIZE
A

 CODE IDENT
15542

 DRAWING NO:
98-PL-300


 REV:
OR

FILE: 98PL300


SCALE: 20:1

SHEET: 1 OF 1

Characterization Test Board



TB-471+



Schematic Diagram

Notes:

1. 50 Ohm SMA Female connectors.
2. PCB Material: Rogers R04350B or its equivalent, Dielectric Constant=3.5, Thickness=.020"

 **Mini-Circuits®**



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-45° to 85°C or -40° to 85°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-65° to 150° C Ambient Environment	Individual Model Data Sheet
Thermal Shock	-55° to 100°C, 100 cycles	MIL-STD-202, Method 107, Condition A-3, except +100°C
Mechanical Shock	1.5Kg, 0.5 ms, 5 shock pulses, Y1 direction only	MIL-STD-883, Method 2002, Condition B, except Y1 direction only
Vibration (Variable Frequency)	50g peak	MIL-STD-883, Method 2007, Condition B
Autoclave	15 psig, 100% RH, 121°C, 96 hours	JESD22-A102, Condition C
HAST	130°C, 85% RH, 96 hours	JESD22-A110
Solderability	10X Magnification	J-STD-002, Para 4.2.5, Test S, 95% Coverage
Solder Reflow Heat	Sn-Pb Eutetic Process: 240°C peak Pb-Free Process: 260°C peak	J-STD-020, Table 4-1, 4-2 and 5-2; Figure 5-1
Moisture Sensitivity: Level 1	Bake at 125°C for 24 hours Soak at 85°C/85% RH for 168 hours, Reflow 3 cycles at 260°C peak	J-STD-020
Marking Resistance to Solvents	Isopropyl alcohol + mineral spirits at 25°C; terpene defluxer at 25°C; distilled water + proylene glycol monomethyl ether +	MIL-STD-202, Method 215



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
	monoethanolamine at 63°C to 70°C	