



Mini-Circuits

COAXIAL

Adapter, SMA-F to SMA-M

SF-SM50+

50Ω DC to 18 GHz

FEATURES

- Flat response
- Excellent VSWR, 1.05:1 typ. up to 12.4 GHz and 1.15:1 typ. up to 18 GHz
- Low cost adapters, available from stock
- Rugged stainless steel body

APPLICATIONS

- Connector saver
- Cable extender



Generic photo used for illustration purposes only

Model No.	SF-SM50+
Case Style	DJ836
Connectors	SMA-F to SMA-M

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

ELECTRICAL SPECIFICATIONS AT 25°C

Parameter	Frequency (GHz)	Min.	Typ.	Max.	Units
Frequency Range		DC		18	GHz
Insertion Loss	DC - 18	—	0.01	—	dB
VSWR	DC-8	—	—	1.15	:1
	DC-12.4	—	—	1.28	
	DC-18	—	—	1.30	

MAXIMUM RATINGS

Parameter	Ratings
Operating temperature	-55°C to 100°C
Storage temperature	-55°C to 100°C

Permanent damage may occur if any of these limits are exceeded.

REV. F
ECO-012138
SF-SM50+
MCL NY
220221






COAXIAL

Adapter, SMA-F to SMA-M

SF-SM50+

Mini-Circuits

OUTLINE DRAWING




OUTLINE DIMENSIONS (Inch/mm)

A	B	C	D	E	wt
--	.36	--	0.72	.312	grams
--	9.14	--	18.29	7.92	3.2

TYPICAL PERFORMANCE DATA

Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)	
		SMA-FEMALE	SMA-MALE
10	0.00	1.00	1.00
50	0.01	1.00	1.00
100	0.01	1.00	1.00
500	0.02	1.01	1.01
1000	0.03	1.01	1.01
2000	0.03	1.01	1.01
3000	0.04	1.02	1.01
4000	0.04	1.03	1.02
5000	0.05	1.05	1.04
6000	0.04	1.07	1.07
7000	0.05	1.09	1.09
8000	0.05	1.12	1.12
9000	0.05	1.14	1.13
10000	0.05	1.14	1.13
11000	0.04	1.13	1.13
12000	0.04	1.11	1.12
13000	0.09	1.09	1.12
15000	0.07	1.08	1.11
16000	0.08	1.08	1.09
18000	0.09	1.06	1.04



NOTES




- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the standard. Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp


Mini-Circuits

Typical Performance Data

FREQUENCY (MHz)	ATTENUATION (dB)	SMA-FEMALE VSWR (:1)	SMA-MALE VSWR (:1)
10	0.00	1.00	1.00
50	0.01	1.00	1.00
100	0.01	1.00	1.00
500	0.02	1.01	1.01
1000	0.03	1.01	1.01
2000	0.03	1.01	1.01
3000	0.04	1.02	1.01
4000	0.04	1.03	1.02
5000	0.05	1.05	1.04
6000	0.04	1.07	1.07
7000	0.05	1.09	1.09
8000	0.05	1.12	1.12
9000	0.05	1.14	1.13
10000	0.05	1.14	1.13
11000	0.04	1.13	1.13
12000	0.04	1.11	1.12
13000	0.09	1.09	1.12
15000	0.07	1.08	1.11
16000	0.08	1.08	1.09
18000	0.09	1.06	1.04

Typical Performance Curves





Weight: 3.2 grams

Dimensions are in inches [mm]. Tolerances: 2 Pl. ± .03; 3 Pl. ± .015 Inches

Notes:

1. Case material: Stainless steel.
2. Case Finish: Passivation or Gold Plating. (See individual model datasheet).
3. For polarity of connector refer individual model data sheet.



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

RF/IF MICROWAVE COMPONENTS



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-55° to 100°C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-55° to 100° C Ambient Environment	Individual Model Data Sheet
Barometric Pressure	100,000 Feet	MIL-STD-202, Method 105, Condition D
Humidity	90% RH, 65°C Units may require bake-out after humidity to restore full performance.	MIL-STD-202, Method 103
Thermal Shock	-65° to 125°C, 5 cycles	MIL-STD-202, Method 107, Condition B
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D
Mechanical Shock	100g, 6ms sawtooth, 3 shocks each direction 3 axes (total 18)	MIL-STD-202, Method 213, Condition I