

*Typical Performance Data*

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	29.91	1.23
0.02	29.91	1.23
0.04	29.91	1.23
0.06	29.91	1.23
0.08	29.91	1.23
0.10	29.91	1.23
0.20	29.90	1.23
0.40	29.91	1.23
0.60	29.90	1.23
0.80	29.90	1.23
1.00	29.90	1.23
1.20	29.91	1.23
1.40	29.90	1.23
1.60	29.90	1.23
1.80	29.90	1.23
2.00	29.90	1.23
3.00	29.89	1.23
4.00	29.88	1.23
5.00	29.90	1.23
6.00	29.88	1.23
7.00	29.87	1.23
8.00	29.86	1.23
9.00	29.88	1.23
10.0	29.86	1.22
11.0	29.86	1.22
12.0	30.05	1.22
13.0	30.16	1.21
14.0	30.04	1.21
15.0	30.10	1.21
16.0	30.13	1.20
17.0	30.08	1.20
18.0	30.16	1.19
19.0	30.18	1.19
20.0	30.30	1.18
21.0	30.23	1.18
22.0	30.14	1.18
23.0	30.15	1.17
24.0	30.22	1.17
25.0	30.17	1.17
26.0	30.33	1.16
27.0	30.47	1.16
28.0	30.54	1.15
29.0	30.42	1.15
30.0	30.28	1.14
31.0	30.53	1.14
32.0	30.49	1.13
33.0	30.18	1.12
34.0	29.99	1.12
35.0	29.88	1.12
36.0	30.08	1.11
37.0	29.87	1.12
38.0	29.80	1.11
39.0	29.88	1.11
40.0	30.10	1.11
41.0	30.06	1.12
42.0	29.70	1.12
43.0	29.66	1.12
43.5	29.70	1.12