


REVISIONS					
REV	ECN No.	DESCRIPTION	DATE	DR	AUTH
OR	M145645	NEW RELEASE	03/18/14	AV	RS
A	M146006	TB-722-F+, WAS TB-722-N+	04/07/14	ITG	IL

SUGGESTED MOUNTING CONFIGURATION
FOR MT1817 CASE STYLE, "14SW02" PIN CODE



NOTES:

- TRACE WIDTH IS SHOWN FOR ROGERS R04350B WITH DIELECTRIC THICKNESS .010" ± .001". COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH AND GAP MAY NEED TO BE MODIFIED.
- BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.


-  DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER).
-  DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK.

UNLESS OTHERWISE SPECIFIED	INITIALS		DATE
DIMENSIONS ARE IN INCHES	DRAWN	AV	03/13/14
TOLERANCES ON:	CHECKED	IL	03/18/14
2 PL DECIMALS ±	APPROVED	RS	03/18/14
3 PL DECIMALS ± .005			
ANGLES ±			
FRACTIONS ±			

 **Mini-Circuits®** 13 Neptune Avenue
Brooklyn NY 11235

PL, 14SW02, 75, MT1817, TB-722-F+

SIZE A	CODE IDENT 15542	DRAWING NO: 98-PL-417	REV: A
FILE: 98PL417	SCALE: 12:1	SHEET: 1 OF 1	

 Mini-Circuits®
THIS DOCUMENT AND ITS CONTENTS ARE THE PROPERTY OF MINI-CIRCUITS. EXCEPT FOR USE EXPRESSLY GRANTED, IN WRITING, TO ITS VENDORS, VENDEE AND THE UNITED STATES GOVERNMENT, MINI-CIRCUITS RESERVES ALL PROPRIETARY DESIGN, USE, MANUFACTURING AND REPRODUCTION RIGHTS THERETO. THESE CONTENTS SHALL NOT BE USED, DUPLICATED OR DISCLOSED TO ANY OUTSIDE PARTY, IN WHOLE OR IN PART, WITHOUT WRITTEN PERMISSION OF MINI-CIRCUITS.